ROPE 03

ANCHOR & MOORING ROPES

Silver Polyethylene Anchor Rope	3.02
Nylon Rope	3.02
Polyester Rope	3.03
Dock Lines	3.03
Fender Lanyards	3.03
Anchor Rope & Chain Kits	3.04

YACHTING ROPE & CORDS

Shock Cord	3.04
Dinghy Lines	3.04
VB Cord	3.05
Starter Cord	3.05
Polyester Yacht Ropes	3.05
Spectra Ropes	3.06
Soft Rope Shackles	

ROPE TOOLS

Hot Knife	3.06
Rope Splicing Fids	3.06





03 - ROPE

Silver 3 Strand Anchor Rope with Thimble - 50m Coils

Polyethylene rope is extremely versatile for fishing and marine applications and is most commonly used as anchor rope for trailer boats. UV-stabilised for the marine environment.

- Floats with slack line for easy pickup of mooring lines.
- 100% polyethylene with high abrasion resistance in a medium soft lay.



• 50m coils supplied with a stainless steel thimble spliced at one end.

Dia (mm)	Length (m)	Breaking Strain (kg)
6	50	390
8	50	680
10	50	1050
12	50	1250
14	50	1580
	6 8 10 12	6 50 8 50 10 50 12 50

Silver 3 Strand Anchor Rope - Hanks

Polyethylene 3 strand anchor rope 50m hanks supplied with a stainless steel thimble spiced at one end, supplied in easy to display hanks.

- UV-stabilised for the marine environment.
- Suitable for general marine applications such as anchor rope.
- Floats with slack line for easy pickup of mooring lines.
- 100% polyethylene with high abrasion resistance in a medium soft lay.



Part No.	Dia (mm)	Length (m)	Breaking Strain (kg)
JPW627	8	50	680
JPW628	10	50	1050

Silver 3 Strand Anchor Rope - Spools

Silver rope is extremely versatile for fishing and marine applications and is most commonly used as anchor rope in trailer boats.

- Will float with slack line for easy pickup of mooring lines.
- 100% polyethylene staple and UV-stabilised for the marine environment.
- Made to Australian standards AS4142.2-1993.
- High abrasion resistance and medium soft lay for easy splicing.

Part No.	Dia (mm)	Length (m)	Breaking Strain (kg)
JPW606	6	250	370
JPW607	8	250	600
JPW608	10	150	940

Silver 3 Strand Anchor Rope - Large Coils

Silver rope is extremely versatile for fishing and marine applications and is most commonly used as anchor rope in trailer boats. Silver rope will float with slack line for easy pickup of mooring lines. 100% polyethylene staple and UV-stabilised for the marine environment.



- Made to Australian standards AS4142.2-1993.
- Resistant to grease, oil and water.

· High abrasion resistance and medium soft lay for easy splicing.

Part No.	Dia (mm)	Length (m)	Breaking Strain (kg)
JPW612	10	250	1050
JPW609	12	100	1250
JPW613	12	250	1250
JPW614	14	250	1580
JPW615	16	125	2080
JPW616	18	125	2560
JPW617	20	125	3200
JPW618	22	125	3690
JPW619	24	125	4310
JPW620	28	125	5830
JPW621	32	125	7620
JPW622	36	125	9630

Nylon 3 Strand Rope - Large Coils

High quality nylon rope using 100% high strength nylon fibres which has nearly double the strength of silver rope.

- Excellent high resistance against abrasions and has a stretch factor.
- Used as a high strength anchor winch rope and general purpose.
- Made to Australian Standards (AS4142.2).
- Does not float will sink.





Suitable for rope chain gypsy on anchor winches

Part No.	Dia (mm)	Length (m)	Breaking Strain (kg)
JPW645	12	50	3200
JPW646	12	100	3200
JPW648	12	200	3200
JPW647	14	50	4380
JPW649	14	100	4380
JPW650	16	100	5700
JPW651	18	100	7100

JPW MARINE

Polyester Ropes - 3 Strand Black

High quality polyester rope, sold by the roll; ideal for use as dock lines or for high strength anchor winch rope.

- The line is soft to the hand and easy to handle.
- Great strength, abrasion resistance and has a stretch factor.



Part No.	Dia (mm)	Length (m)	Breaking Strain (kg)
JPW663	12	100	1500
JPW664	12	200	1500
JPW665	14	100	2700
JPW666	16	100	3000
JPW667	18	150	4200

Dock Lines - Double Braided Polyester

Dock lines made from high quality UV-stabilised 16-strand double braid black polyester with a professionally hand-spliced 300mm loop with whipped end to prevent fraying.

- Pre-made in various lengths to suit your requirements.
- Strong and soft to handle.



Supplied in a mesh bag for easy storage

Part No.	Diameter (mm)	Length (m)	Breaking Strain (kg)
JPW6850	10	6	1600
JPW6851	10	10	1600
JPW6852	12	6	2000
JPW6853	12	10	2000
JPW6854	14	10	2900
JPW6855	14	15	2900
JPW6856	16	10	3800
JPW6857	16	15	3800
JPW6858	18	10	4500
JPW6859	18	16	4500
JPW6860	20	16	5100

Dock Lines - Double Braided Nylon

White, soft and easy to handle. Great elasticity, good abrasion resistance and high strength. Spliced with a large loop on one end to throw over a cleat or bollard.



Part No.	Dia (mm)	Length (m)	Breaking Strain (kg)
JPW6870	10	4.5	1587
JPW6871	10	7.6	1587

Fender Lanyard - Double Braided Polyester Blue

Fender lines/lanyards made from high quality UV-stabilised 16-strand double braid blue polyester, professionally

hand-spliced 150mm loop with

whipped end to prevent fraying.

• Soft on hands and easy to handle.



Supplied in a hank for easy storage

Part No.	Diameter (mm)	Length (m)	Colour
JPW6874	10	1.8	Blue

Fender Lanyards - Double Braided Polyester Black

Fender lines/lanyards made from high quality UV-stabilised 16-strand double braid black polyester, professionally hand-spliced 300mm loop with whipped end to prevent fraying.

· Soft on hands and easy to handle.





Supplied in a retail hang sell plastic bag

Part No.	Diameter (mm)	Length (m)	Colour	Breaking Strain (kg)
JPW6862	10	2	Black	1600
JPW6863	14	2	Black	2900
JPW6864	14	3	Black	2900

03 - ROPE

Anchor Rope and Chain Kits - for Windlasses

Anchor rope and chain kits, 3 strand nylon rope pre-spliced to short link chain to suit anchor windlasses.

- Note: Galvanised short link chain is calibrated to suit windlasses.
- Rope and chain kits can be made to order upon request.



Part No.	Chain		Rope	
	Size (mm)	Length (m)	Dia (mm)	Length (m)
JPW1020	6	10	12.7	50
JPW1026	6	10	12.7	100
JPW1021	6	20	12.7	100
JPW1024	8	10	12.7	50
JPW1025	8	10	12.7	100
JPW1022	8	10	14.2	50
JPW1023	8	10	14.2	100
JPW1023	8	10	14.2	100

Anchor Rope and Chain Kit - for Drum Winches

Best suited for drum winches, this rope and chain has been prespliced for added convenience.

- 8 plait nylon rope.
- Short link galvanised chain.



Part No.	Chain		Rope	
Fall NO.	Size (mm)	Length (m)	Dia (mm)	Length (m)
JPW1031	6	10	12	50

Shock Cord

Superior quality marine-grade shock cord featuring polyester yarn outer covering and pure natural latex rubber ribbon interior. This quality shock cord has high stretch capability, UV resistance, is extremely durable, colour-fast and won't absorb water.

- Shock cord is NOT bungy cord (it has no break strain rating, do not overstretch).
- Supplied in 50m or 100m flanged reels.



Part No:	Colour	Dia (mm)	Length (m)
JPW13179	Black	3	100
JPW13180	White/Blue	3	100
JPW13181	White/Blue	4	100
JPW13182	Black	4	100
JPW13183	White/Blue	5	100
JPW13184	Black	5	100
JPW13185	White/Blue	6	100
JPW13186	Black	6	100
JPW13187	White/Blue	7	100
JPW13188	Black	7	100
JPW13189	Black	8	100
JPW13190	White/Blue	8	100
JPW13191	White/Blue	10	50
JPW13192	Black	10	50

UV Resistant Dinghy Lines - 8 Strand

8-strand dinghy line, braided sheen finish rope, in natural white or black.

- Ideal for dinghy control lines, flag halyards, etc.
- Black is UV treated polypropylene.
- White rope is polyester.







Part No:	Colour	Dia (mm)	Length (m)	Break Strain
JPW13249	White	4	400	318kg
JPW13241	White	5	100	420kg
JPW13250	White	5	250	507kg
JPW13253	Black	5	250	507kg
JPW13251	White	6	250	710kg
JPW13252	White	8	200	1490kg

VB Cord - 8 Strand

VB cord 2mm, 2.5mm and 3mm diameter 8-strand solid colour UV-treated polypropylene VB cord.





Part No:	Colour	Dia (mm)	Length (m)
JPW13100	Natural White	2	100
JPW13102	Black	2	500
JPW13101	Natural White	2	500
JPW13114	Black	2.5	100
JPW13112	Blue	2.5	100
JPW13111	Natural White	2.5	100
JPW13113	Red	2.5	100
JPW13110	Yellow	2.5	100
JPW13115	**Random	2.5	500
JPW13116	Natural White	2.5	1000
JPW13118	Black	3	100
JPW13119	Blue	3	100
JPW13121	Green	3	100
JPW13122	Natural White	3	100
JPW13120	Red	3	100
JPW13117	Yellow	3	100
JPW13126	Black	3	500
JPW13127	Green	3	500
JPW13123	Natural White	3	500

Nylon Starter Cord

- Motor starter cord.
- 8 plait nylon cord for outboard motors.



Part No:	Colour	Dia (mm)	Length (m)
JPW13000	White	3	100
JPW13010	White	4	100
JPW13020	White	5	100

Polyester Yacht Ropes - 16 Strand Double Braid

Double braid is extremely strong, flexible, and has a low stretch factor, whilst remaining soft and easy to handle, making it ideal for sheet lines, halyards, control lines or general uses.

• It has a plaited polyester core and sheen cover made from continuous filament 16-strand polyester.





Part No:	Colour	Dia (mm)	Length (m)	Break Strain
JPW14148	White/Blue	6	200	990kg
JPW14149	White/Green	6	200	990kg
JPW14150	White/Gold	6	200	990kg
JPW14151	White/Red	6	200	990kg
JPW14153	White/Gold	8	200	1600kg
JPW14154	White/Blue	8	200	1600kg
JPW14155	White/Green	8	200	1600kg
JPW14156	White/Red	8	200	1600kg
JPW14157	White/Gold	10	100	2200kg
JPW14158	White/Red	10	100	2200kg
JPW14159	White/Blue	10	100	2200kg
JPW14160	White/Green	10	100	2200kg
JPW14161	White/Gold	12	100	3400kg
JPW14163	White/Green	12	100	3400kg
JPW14164	White/Red	12	100	3400kg
JPW14165	White/Blue	12	100	3400kg
JPW14166	White/Red	14	100	4800kg
JPW14167	White/Blue	14	100	4800kg
JPW14168	White/Gold	14	100	4800kg



03 - ROPE

Spectra Ropes

UV-resistant high strength, high performance, lightweight, very low stretch rope made from the finest materials

- 100% polyester jacket with extremely low stretch spectra core.
- Ideal for halyards, sheets, control lines, kite boarding lines, anywhere low stretch and high strength is required.
- Variety of bright attractive solid colours all with black trace.
- 100 metre flanged reels, diameter ranging from 2mm to 8mm.



Part No.	Colour	Dia (mm)	Length (m)	Break Strain (kg)
JPW14005	Red	2	100	260
JPW14006	Yellow	2	100	260
JPW14007	Green	2	100	260
JPW14008	Blue	2	100	260
JPW14009	Black	2	100	260
JPW14010	Red	3	100	400
JPW14011	Yellow	3	100	400
JPW14012	Green	3	100	400
JPW14013	Blue	3	100	400
JPW14014	Black	3	100	400
JPW14015	Red	4	100	900
JPW14016	Yellow	4	100	900
JPW14017	Green	4	100	900
JPW14018	Blue	4	100	900
JPW14019	Black	4	100	900
JPW14020	Red	5	100	970
JPW14021	Yellow	5	100	970
JPW14022	Green	5	100	970
JPW14023	Blue	5	100	970
JPW14024	Black	5	100	970
JPW14025	Red	6	100	1700
JPW14026	Yellow	6	100	1700
JPW14027	Green	6	100	1700
JPW14028	Blue	6	100	1700
JPW14029	Black	6	100	1700
JPW14030	Red	8	100	3300
JPW14031	Yellow	8	100	3300
JPW14032	Green	8	100	3300
JPW14033	Blue	8	100	3300
JPW14034	Black	8	100	3300

Soft Rope Shackles

The soft rope shackle is made with UHMWPE (Ultra high molecular weight polyethylene) and ideal for hooking up halyards, connecting sheets or attaching blocks.

- Lighter than a metal shackle without losing any strength.
- Fast, secure connection and simple to use.
- · Highly resistant to abrasion.
- · Locks closed when under load.
- · Requires no tools to undo.




Part No.	Width (mm)	Total Length (mm)	Breaking Strain (kg)
JPW4972	6	100	3300
JPW4973	8	100	5500
JPW4974	10	150	8100
JPW4975	12	150	12500
JPW4976	14	150	15000

Hot Knife

60 watt hot knife rope cutter comes with R blade, wire cleaning brush.

- Heat seals rope to avoid fraying ends.
- Voltage: 220V 240V



Rope Splicing Fids

Stainless steel hollow groove splicing fids, to assist in splicing ropes. • Solid plastic handle.



Part No:	Dimensions; L x W (mm)	Handle Colour
JPW10012	170 x 20	Blue
JPW10013	280 x 32	Blue
JPW10014	380 x 38	Yellow