ISSUED by ICON Plastics Pty Ltd

PLASTIC GUNWALE CLEANER

1. IDENTIFICATION OF THE SUBSTANCE AND COMPANY UNDERTAKING

Product Name Product Use	Plastic Gunwale Cleaner (PUC) Plastic Surface Cleaner (MARINE)
Company Name	ICON Plastics Pty Ltd ABN 89 071 392 366 19-21 Hallam Rd South Hallam VIC 3803 Australia
Address	
Emergency Tel. Telephone	+61 3 8796 9277 +61 3 8796 9277
Fax	+61 39703 1478
Web	Iconplastics.com.au
Other Names	

SECTION 2 - HAZARDS IDENTIFICATION

Statement of Hazardous Nature

This product is classified as: Xn, Harmful. Xi, Irritating. F, Flammable. Hazardous according to the criteria of SWA.

Dangerous according to Australian Dangerous Goods (ADG) Code, IATA and IMDG/IMSBC criteria.

Risk Phrases: R10, R20/21/22, R36/38. Flammable. Harmful by inhalation, in contact with skin, and if swallowed. Irritating to eyes and skin.

Safety Phrases: S16, S20, S23, S38, S51, S24/25, S37/39. Keep away from sources of ignition - No smoking. When using, do not eat or drink. Do not breathe vapours or mists. In case of insufficient ventilation, wear suitable respiratory equipment. Use only in well ventilated areas. Avoid contact with skin and eyes. Wear suitable gloves and eye/face protection.

SUSMP Classification: S6

ADG Classification: Class 3: Flammable liquids. **UN Number:** 1993, FLAMMABLE LIQUID, N.O.S.



GHS Signal word: WARNING

HAZARD STATEMENT:

- H226: Flammable liquid and vapour.
- H302: Harmful if swallowed.
- H312: Harmful in contact with skin.
- H315: Causes skin irritation.
- H320: Causes eye irritation.
- H332: Harmful if inhaled.
- H335: May cause respiratory irritation.

PREVENTION

P102: Keep out of reach of children.

- P210: Keep away from heat, sparks, open flames and hot surfaces. No smoking.
- P233: Keep container tightly closed.
- P242: Use only non-sparking tools.
- P261: Avoid breathing fumes, mists, vapours or spray.
- P262: Do not get in eyes, on skin, or on clothing.
- P264: Wash contacted areas thoroughly after handling.
- P270: Do not eat, drink or smoke when using this product.
- P271: Use only outdoors or in a well ventilated area.
- P281: Use personal protective equipment as required.



ISSUED by ICON Plastics Pty Ltd

PLASTIC GUNWALE CLEANER

RESPONSE

P362: Take off contaminated clothing and wash before reuse.

P301+P312: IF SWALLOWED: Call a POISON CENTRE or doctor if you feel unwell.

P301+P330+P331: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P302+P352: IF ON SKIN: Wash with plenty of soap and water.

P304+P340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P332+P313: If skin irritation occurs: Get medical advice.

P337+P313: If eye irritation persists: Get medical advice.

P370+P378: In case of fire, use carbon dioxide, dry chemical, foam, water fog. Alcohol resistant foam is the preferred firefighting medium but, if it is not available, normal foam can be used.

STORAGE

P403: Store in a well-ventilated place.

P402+P404: Store in a dry place. Store in a closed container.

DISPOSAL

P501: If they can not be recycled, dispose of contents to an approved waste disposal plant and containers to landfill (see Section 13 of this SDS).

EMERGENCY OVERVIEW

Physical Description & Colour: Clear, colourless liquid.

Odour: Mild alcohol-like odour.

Major Health Hazards: 2-butoxyethanol is a severe eye irritant. Results of skin irritation studies are conflicting; however, it is considered to be a mild to moderate skin irritant in test animals. Contact dermatitis has been reported in a few cases. It is well absorbed via the inhalational, oral and dermal routes. This product is harmful by inhalation, in contact with skin, and if swallowed, irritating to eyes and skin.

SECTION 3 - COMPOSITION/INFORMATION ON INGREDIENTS

Ingredients	CAS No STEL (mg	Conc,% /m³)	TWA (mg/	m³)
2-Butoxyethanol	111-76-2	10-30	96.9	242
Isopropanol	67-63-0	10-30	983	1230
Other non hazardous ingredients	secret	to 100	not set	not

set

This is a commercial product whose exact ratio of components may vary slightly. Minor quantities of other non hazardous ingredients are also possible.

The SWA TWA exposure value is the average airborne concentration of a particular substance when calculated over a normal 8 hour working day for a 5 day working week. The STEL (Short Term Exposure Limit) is an exposure value that may be equalled (but should not be exceeded) for no longer than 15 minutes and should not be repeated more than 4 times per day. There should be at least 60 minutes between successive exposures at the STEL. The term "peak "is used when the TWA limit, because of the rapid action of the substance, should never be exceeded, even briefly.

SECTION 4 - FIRST AID MEASURES

General Information:

You should call The Poisons Information Centre if you feel that you may have been poisoned, burned or irritated by this product. The number is 13 1126 from anywhere in Australia (0800 764 766 in New Zealand) and is available at all times. Have this SDS with you when you call.

Inhalation: If symptoms of poisoning become evident, contact a Poisons Information Centre, or call a doctor at once. Remove source of contamination or move victim to fresh air. If breathing is difficult, oxygen may be beneficial if administered by trained personnel, preferably on a doctor's advice. DO NOT allow victim to move about unnecessarily. Symptoms of pulmonary oedema can be delayed up to 48 hours after exposure.

ISSUED by ICON Plastics Pty Ltd

PLASTIC GUNWALE CLEANER

Skin Contact: Wash gently and thoroughly with warm water (use non-abrasive soap if necessary) for 10-20 minutes or until product is removed. Under running water, remove contaminated clothing, shoes and leather goods (e.g. watchbands and belts) and completely decontaminate them before reuse or discard. If irritation persists, repeat flushing and seek medical attention.

Eye Contact: Immediately flush the contaminated eye(s) with lukewarm, gently flowing water for 15 minutes or until the product is removed, while holding the eyelid(s) open. Take care not to rinse contaminated water into the unaffected eye or onto the face. Obtain medical attention immediately. Take special care if exposed person is wearing contact lenses.

Ingestion: If swallowed, do NOT induce vomiting. Wash mouth with water and contact a Poisons Information Centre, or call a doctor.

SECTION 5 - FIRE FIGHTING MEASURES

Fire and Explosion Hazards: The major hazard in fires is usually inhalation of heated and toxic or oxygen deficient (or both), fire gases. There is a moderate risk of an explosion from this product if commercial quantities are involved in a fire. Firefighters should take care and appropriate precautions. Any explosion will likely spread the fire to surrounding materials. Water spray may be used to cool drums involved in a fire, reducing the chances of an explosion. Vapours from this product are heavier than air and may accumulate in sumps, pits and other low-lying spaces, forming potentially explosive mixtures. They may also flash back considerable distances.

This product is likely to decompose only after heating to dryness, followed by further strong heating. Fire decomposition products from this product are likely to be harmful if inhaled. Take suitable protective measures.

Extinguishing Media: In case of fire, use carbon dioxide, dry chemical, foam, water fog. Alcohol resistant foam is the preferred firefighting medium but, if it is not available, normal foam can be used. Try to contain spills, minimise spillage entering drains or water courses.

Fire Fighting: If a significant quantity of this product is involved in a fire, call the fire brigade. There is a danger of a violent reaction or explosion if significant quantities of this product are involved in a fire. Recommended personal protective equipment is full fire kit and breathing apparatus.

Flash point: 34°C	
Upper Flammability Limit: Does not burn.	
Lower Flammability Limit: Does not burn.	
Autoignition temperature: Does not burn.	
Flammability Class: Flammable Category	3 (GHS); Flammable (AS1940)

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Accidental release: In the event of a major spill, prevent spillage from entering drains or water courses. Evacuate the spill area and deny entry to unnecessary and unprotected personnel. Immediately call the Fire Brigade. Wear full protective clothing including eye/face protection. All skin areas should be covered. See below under Personal Protection regarding Australian Standards relating to personal protective equipment. Suitable materials for protective clothing include Viton, Nitrile, butyl rubber, PE/EVAL, Responder. Eye/face protective equipment should comprise as a minimum, protective goggles. If there is a significant chance that vapours or mists are likely to build up in the cleanup area, we recommend that you use a respirator. Usually, no respirator is necessary when using this product. However, if you have any doubts consult the Australian Standard mentioned below (section 8). Otherwise, not normally necessary.

Stop leak if safe to do so, and contain spill. Absorb onto sand, vermiculite or other suitable absorbent material. If spill is too large or if absorbent material is not available, try to create a dike to stop material spreading or going into drains or waterways. Avoid using sawdust or other combustible material. Any electrical equipment should be non-sparking. Any equipment capable of building an electrostatic charge should be electrically grounded. Sweep up and shovel or collect recoverable product into labelled containers for recycling or salvage, and dispose of promptly. Recycle containers wherever possible after careful cleaning. After spills, wash area preventing runoff from entering drains. If a significant quantity of material enters drains, advise emergency services. This material may be suitable for approved landfill. Ensure legality of disposal by consulting regulations prior to disposal. Thoroughly launder protective

ISSUED by ICON Plastics Pty Ltd

PLASTIC GUNWALE CLEANER

clothing before storage or re-use. Advise laundry of nature of contamination when sending contaminated clothing to laundry.

SECTION 7 - HANDLING AND STORAGE

Handling: Keep exposure to this product to a minimum, and minimise the quantities kept in work areas. Check Section 8 of this SDS for details of personal protective measures, and make sure that those measures are followed. The measures detailed below under "Storage" should be followed during handling in order to minimise risks to persons using the product in the workplace. Also, avoid contact or contamination of product with incompatible materials listed in Section 10.

Storage: This product is a Scheduled Poison. Observe all relevant regulations regarding sale, transport and storage of this schedule of poison. Store in a cool, well ventilated area, and make sure that surrounding electrical devices and switches are suitable. Check containers periodically for leaks. Containers should be kept closed in order to minimise contamination and possible evaporation. Make sure that the product does not come into contact with substances listed under "Incompatibilities" in Section 10. If you keep more than 10000kg or L of Dangerous Goods of Packaging Group III, you may be required to license the premises or notify your Dangerous Goods authority. If you have any doubts, we suggest you contact your Dangerous Goods authority in order to clarify your obligations. Check packaging - there may be further storage instructions on the label.

SECTION 8 - EXPOSURE CONTROLS AND PERSONAL PROTECTION

The following Australian Standards will provide general advice regarding safety clothing and equipment:

Respiratory equipment: **AS/NZS 1715**, Protective Gloves: **AS 2161**, Occupational Protective Clothing: AS/NZS 4501 set 2008, Industrial Eye Protection: **AS1336** and **AS/NZS 1337**, Occupational Protective Footwear: **AS/NZS2210**.

SWA Exposure Limits	TWA (mg/m³)	STEL (mg/m ³)
2-Butoxyethanol	96.9	242
Isopropanol	983	1230

No special equipment is usually needed when occasionally handling small quantities. The following instructions are for bulk handling or where regular exposure in an occupational setting occurs without proper containment systems.

Ventilation: This product should only be used in a well ventilated area. If natural ventilation is inadequate, use of a fan is suggested.

Eye Protection: Protective glasses or goggles should be worn when this product is being used. Failure to protect your eyes may cause them harm. Emergency eye wash facilities are also recommended in an area close to where this product is being used.

Skin Protection: Prevent skin contact by wearing impervious gloves, clothes and, preferably, apron. Make sure that all skin areas are covered. See below for suitable material types.

Protective Material Types: We suggest that protective clothing be made from the following materials: Viton, nitrile, butyl rubber, PE/EVAL, Responder.

Respirator: Usually, no respirator is necessary when using this product. However, if you have any doubts consult the Australian Standard mentioned above. Otherwise, not normally necessary. Eyebaths or eyewash stations and safety deluge showers should, if practical, be provided near to where this product is being handled commercially.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES:

Clear, colourless liquid. Mild alcohol-like odour. Not available. No specific data. Liquid at normal temperatures. Water component. 2.37 kPa at 20°C (water vapour pressure). As for water. 0.93
Completely soluble in water.

SAFETY DATA SHEET ISSUED by ICON Plastics Pty Ltd PLASTIC GUNWALE CLEANER

pH:	No data.
Volatility:	No data.
Odour Threshold:	No data.
Evaporation Rate:	As for water.
Coeff Oil/water Distribution:	No data
Autoignition temp:	Does not burn.

SECTION 10 - STABILITY AND REACTIVITY

Reactivity: This product is unlikely to react or decompose under normal storage conditions. However, if you have any doubts, contact the supplier for advice on shelf life properties.

Conditions to Avoid: This product should be kept in a cool place, preferably below 30°C. Keep containers tightly closed. Containers should be kept dry. Keep containers and surrounding areas well ventilated. Keep away from sources of sparks or ignition. Handle and open containers carefully. Any electrical equipment in the area of this product should be flame proofed.

Incompatibilities: oxidising agents.

Fire Decomposition: This product is likely to decompose only after heating to dryness, followed by further strong heating. Combustion forms carbon dioxide, and if incomplete, carbon monoxide and possibly smoke. Water is also formed. Carbon monoxide poisoning produces headache, weakness, nausea, dizziness, confusion, dimness of vision, disturbance of judgment, and unconsciousness followed by coma and death.

Polymerisation: This product will not undergo polymerisation reactions.

SECTION 11 - TOXICOLOGICAL INFORMATION

Toxicity: 2-butoxyethanol is a severe eye irritant. Results of skin irritation studies are conflicting; however, it is considered to be a mild to moderate skin irritant in test animals. Contact dermatitis has been reported in a few cases. It is well absorbed via the inhalational, oral and dermal routes. Absorption studies in various species, including humans, have shown that 2-butoxyethanol is rapidly absorbed through the skin, including absorption from aqueous solutions. The respiratory uptake in volunteers in inhalational studies was approximately 57-78% of the inspired amount. Human studies indicate that dermal absorption of vapour is approximately 20% of the total vapour uptake. Following absorption, it is widely distributed throughout the body. The ingestion of large quantities of 2-butoxyethanol may result in coma, metabolic acidosis, shock and respiratory distress.

The main effect observed in both acute and repeated dose animal toxicity studies is haematotoxicity, with the principal haemolytic agent being BAA the major metabolite. Effects other than haemolysis which have been observed in repeated dose studies include changes to the liver, kidney, spleen and thymus, with these effects considered secondary to haemolysis as they are seen at levels at or above haematotoxic doses.

In fertility studies, minor changes in sperm concentration and the oestrous cycle were noted in a drinking water rat study . 2-butoxyethanol has tested negative in a wide variety of well conducted in vitro assays, including gene mutation, chromosomal aberration and DNA effect assays.

There is no data to hand indicating any particular target organs.

POTENTIAL HEALTH EFFECTS

Inhalation:

Short Term Exposure: Available data shows that this product is harmful, but symptoms are not available. In addition product may be mildly irritating, although unlikely to cause anything more than mild transient discomfort.

Long Term Exposure: No data for health effects associated with long term inhalation.

Skin Contact:

Short Term Exposure: Available data shows that this product is harmful, but symptoms are not available. In addition product is a skin irritant. Symptoms may include itchiness and reddening of contacted skin. Other symptoms may also become evident, but all should disappear once exposure has ceased.

Long Term Exposure: No data for health effects associated with long term skin exposure.

ISSUED by ICON Plastics Pty Ltd

PLASTIC GUNWALE CLEANER

Eye Contact:

Short Term Exposure: This product is an eye irritant. Symptoms may include stinging and reddening of eyes and watering which may become copious. Other symptoms may also become evident. If exposure is brief, symptoms should disappear once exposure has ceased. However, lengthy exposure or delayed treatment may cause permanent damage.

Long Term Exposure: No data for health effects associated with long term eye exposure.

Ingestion:

Short Term Exposure: Significant oral exposure is considered to be unlikely. Available data shows that this product is harmful, but symptoms are not available. However, this product is an oral irritant. Symptoms may include burning sensation and reddening of skin in mouth and throat. Other symptoms may also become evident, but all should disappear once exposure has ceased.

Long Term Exposure: No data for health effects associated with long term ingestion.

Carcinogen Status:

SWA: No significant ingredient is classified as carcinogenic by SWA.

NTP: No significant ingredient is classified as carcinogenic by NTP.

IARC: 2-butoxyethanol is Class 3 - unclassifiable as to carcinogenicity to humans.

Isopropanol is Class 3 - unclassifiable as to carcinogenicity to humans.

See the IARC website for further details. A web address has not been provided as addresses frequently change.

CLASSIFICATION OF HAZARDOUS INGREDIENTS

Ingredient

Risk Phrases

No ingredient mentioned in the HSIS Database is present in this product at hazardous concentrations.

SECTION 12 - ECOLOGICAL INFORMATION

Insufficient data to be sure of status. Expected to not be an environmental hazard.

Biodegradation studies indicate that 2-butoxyethanol will be readily degraded by micro-organisms present at sewage treatment plants. Ready biodegradability tests showed that it achieved a biodegradation rate of greater than 77% after 3 days and 100% after 7 days. A 20-day biochemical oxygen demand test and an OECD 28-day closed bottle test gave it degradation rates of 75% and 88% respectively. Literature data confirm these results.

SECTION 13 - DISPOSAL CONSIDERATIONS

Disposal: This product may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. If it has been contaminated, it may be possible to reclaim the product by filtration, distillation or some other means. If neither of these options is suitable in-house, consider controlled incineration, or contact a specialist waste disposal company.

SECTION 14 - TRANSPORT INFORMATION

Dangerous according to Australian Dangerous Goods (ADG) Code, IATA and IMDG/IMSBC criteria.

UN Number: 1993, FLAMMABLE LIQUID, N.O.S. Hazchem Code: •3Y Special Provisions: 223, 274 Limited quantities: ADG 7 specifies a Limited Quantity value of 5 L for this class of product. Dangerous Goods Class: Class 3: Flammable liquids. Packaging Group: III Packaging Method: P001, IBC03, LP01

Class 3 Flammable Liquids shall not be loaded in the same vehicle or packed in the same freight container with Classes 1 (Explosives), 2.1 (Flammable Gases where flammable liquids and flammable gases are both in bulk), 2.3 (Toxic Gases), 4.2 (Spontaneously Combustible Substances), 5.1 (Oxidising Agents), 5.2 (Organic Peroxides), 6 (Toxic Substances, except Flammable Liquid is nitromethane), and 7 (Radioactive Substances). They may however be loaded in the same vehicle or packed in the same

ISSUED by ICON Plastics Pty Ltd

PLASTIC GUNWALE CLEANER

freight container with Classes 2.1 (Flammable Gases except where the Flammable Liquids and Flammable Gases are in bulk), 2.2 (Non-Flammable Non-Toxic Gases), 4.1 (Flammable Solids), 4.3 (Dangerous When Wet Substances), 6 (Toxic Substances, where Flammable Liquid is nitromethane), 8 (Corrosive Substances), 9 (Miscellaneous Dangerous Goods), Foodstuffs or foodstuff empties.

SECTION 15 - REGULATORY INFORMATION

AICS: All of the significant ingredients in this formulation are compliant with NICNAS regulations. The following ingredient: 2-Butoxyethanol, is mentioned in the SUSMP.

SECTION 16 - OTHER INFORMATION

This SDS contains only safety-related information. For other data see product literature.

Acronyms:	
ADG Code	Australian Code for the Transport of Dangerous Goods by Road and Rail (7 th edition)
AICS	Australian Inventory of Chemical Substances
SWA	Safe Work Australia, formerly ASCC and NOHSC
CAS number	Chemical Abstracts Service Registry Number
Hazchem Code	Emergency action code of numbers and letters that provide information to emergency services especially firefighters
IARC	International Agency for Research on Cancer
NOS	Not otherwise specified
NTP	National Toxicology Program (USA)
R-Phrase	Risk Phrase
SUSMP	Standard for the Uniform Scheduling of Medicines & Poisons
UN Number	United Nations Number
THIS SDS SUMMARISES OUR BEST KNOWLEDGE OF THE HEALTH AND SAFETY HAZARD INFORMATION OF THE PRODUCT AND HOW TO SAFELY HANDLE AND USE THE PRODUCT IN THE WORKPLACE. EACH USER MUST REVIEW THIS SDS IN THE CONTEXT OF HOW THE PRODUCT WILL BE HANDLED AND USED IN THE WORKPLACE.	
	INFORMATION IS NEEDED TO ENSURE THAT AN APPROPRIATE RISK ASSESSMENT LD CONTACT THIS COMPANY SO WE CAN ATTEMPT TO OBTAIN ADDITIONAL 'LIERS
OUR RESPONSIBILITY FOR PRO	DUCTS SOLD IS SUBJECT TO OUR STANDARD TERMS AND CONDITIONS. A COPY OF

OUR RESPONSIBILITY FOR PRODUCTS SOLD IS SUBJECT TO OUR STANDARD TERMS AND CONDITIONS, A COPY OF WHICH IS SENT TO OUR CUSTOMERS AND IS ALSO AVAILABLE ON REQUEST.

Please read all labels carefully before using product.