



100 Celebrating
YEARS

**AUSTRALIAN OWNED AND
TRUSTED SINCE 1926** 

MARINE FULL SYN 10W-40

Last updated: 18/07/2025 1:59 pm

PRODUCT CODE	PACK SIZE	CARTON QTY
MARFULL10W40001	1L	6
MARFULL10W40004	4L	4

PRODUCT BENEFITS

Marine Full Syn 10W-40 is a premium, full synthetic **NMMA** (National Marine Manufacturers Association) **FC-W®**, licensed and registered marine petrol engine oil. It contains a **FULL ZINC** anti-wear additive package combined with specialised rust inhibitors to provide optimum engine protection in marine and salt water environments.

[Click Here](#) for NMMA Approval Registration Number FB-781778Y

APPLICATION

Marine Full Syn 10W-40 is designed for use in all types of petrol four stroke engines where SAE 10W-40 and SAE 10W-30 oils are specified by the manufacturer. It is ideal for use in personal watercraft/Jetskis such as –

Sea Doo – RX, GTI, GTR, GTX, RX, Wake Series PWC

Yamaha – FX, GP, VX - Series Wave Runners

Kawasaki – STX Series, Ultra Series Jet Skis

Honda – Aquatrax Series

Marine Full Syn 10W-40 can be used in 4 stroke outboard, inboard and stern drive engines where this specification and viscosity are required, such as in -

Honda	Johnson	Hidea	Nissan
Parsun	Suzuki	Tohatsu	Yamaha



Marine Outboard 10W-40 may also be used in other petrol engined vehicles that require engine oils meeting API SL or earlier specification and/or where ILSAC GF-3 is specified. It is also suitable for use in four stroke motorcycles including those with wet clutches. It is not suitable for use in diesel engines.

PRODUCT BENEFITS

- Registered **NMMA FC-W®** approved engine oil
- **Specially Formulated** for protection for marine salt water environments
- **Full Synthetic** base oils for maximum heat resistance and High performance
- **Full Zinc** for maximum wear protection
- Fast start up oil flow with superior high temperature wear protection
- Safe for catalysts and emission control systems
- Suitable for PWC (Personal Water Craft), Inboard and Outboard engines

MANUFACTURER'S (OEM) APPROVALS & INDUSTRY LICENSES

- NMMA FC-W® Registration Number FB-781778Y

PRODUCT PERFORMANCE LEVELS

- API SL
- China National GB 11121-2006
- JASO MA



100 *Celebrating*
YEARS

**AUSTRALIAN OWNED AND
TRUSTED SINCE 1926** 

TYPICAL DATA

Density at 15°C, kg/L	0.871
Viscosity, Kinematic, cSt at 40°C	94
Viscosity, Kinematic, cSt at 100°C	13.6
Viscosity Index	147
Cold Cranking Viscosity, cP at -25°C	6472
Zinc, Mass %	0.132
Phosphorus, Mass %	0.12
Sulphated Ash, Mass %	0.91
Total Base Number (TBN)	7.4