



**100** Celebrating  
**YEARS**

**AUSTRALIAN OWNED AND  
TRUSTED SINCE 1926** 

## MARINE OUTBOARD 4 STROKE 10W-40 (Semi Syn.)

Last updated: 14/04/2025 4:23 pm

PRODUCT CODE	PACK SIZE	CARTON QTY
MAR10W40005	5L	4
MAR10W40020	20L	
MAR10W40205	205L	

### PRODUCT BENEFITS

**Marine Outboard Four Stroke 10W-40** is a premium, semi synthetic **NMMA** (National Marine Manufacturers Association) **FC-W®**, fully licensed and registered petrol engine oil. It contains a **FULL ZINC** anti-wear additive package combined with specialised rust inhibitors to provide optimum engine protection in marine and salt water environments.

### APPROVALS AND LICENSES

[Click Here](#) for NMMA FC-W License Registration Number FB-13811W

### APPLICATION

**Marine Outboard Four Stroke 10W-40** Is designed for use in all types of petrol four stroke outboard engines where SAE 10W-40 and SAE 15W-40 oils are specified including:

Honda Johnson Nissan Yamaha  
Parsun Suzuki Tohatsu

**Marine Outboard Four Stroke 10W-40** is also ideal for use personal water craft (PWC) / inboard & stern drive petrol engines that require this viscosity grade such as:

Honda Kawasaki Sea Yamaha VM  
Doo

**Marine Outboard Four Stroke 10W-40** may also be used in modern petrol-engine cars that require engine oils meeting API SL or earlier specification and/or where ILSAC GF-3 is specified. It is also suitable for use in four stroke motorcycles including those with wet clutches. It is not suitable for use in diesel engines.

**Please Note:** A 58mm cap with pouring tap is available to fit 20 litre packs.  
<https://penriteoil.com.au/products/58mm-plastic-tap>



### PRODUCT BENEFITS

- Specially Formulated for protection for marine salt water environments
- Registered NMMA FC-W® approved oil
- Fast start up oil flow with superior high temperature wear protection
- Full Zinc for maximum wear protection

### MANUFACTURER'S (OEM) APPROVALS & INDUSTRY LICENSES

- NMMA FC-W® Registration Number FB-13811W

### PRODUCT PERFORMANCE LEVELS

- API SL
- China National GB 11121-2006
- JASO MA
- NMMA FC-W®



**100** *Celebrating*  
**YEARS**

**AUSTRALIAN OWNED AND  
TRUSTED SINCE 1926** 

**TYPICAL DATA**

Colour	Amber
Density at 15°C, kg/L	0.871
Viscosity, Kinematic, cSt at 40°C	94
Viscosity, Kinematic, cSt at 100°C	13.6
Viscosity Index	147
Cold Cranking Viscosity, cP at -25°C	6472
Zinc, Mass %	0.132
Phosphorus, Mass %	0.12
Sulphated Ash, Mass %	0.91
Total Base Number (TBN)	7.4